

Introduction

The 2600 range comprises modular analogue audio and video equipment in a 1U or 2U format with each module independently powered. Designed to the highest specifications and meeting all relevant international standards, modules can be used individually or mixed with others in the range to increase the functionality.



Description

Widely used in outside broadcast vehicles and in flyaway cases due to their compact, rugged and dependable features.

The 5AV2645 2U rack-mounting frame takes up to 9 modules together with their associated rear connector units, the 5AV2641 1U rack-mounting frame up to 4 modules and the 5AV2642 portable case up to 2 modules. (Versions of the 5AV2642 portable case with integral XLRs for audio applications are also available. See the 5AV2642X data sheet.)

The frames distribute mains voltage power internally to each module. Modules incorporate independent power supplies to maximise reliability and isolation between modules.

To meet CE marking requirements, any vacant position in a frame needs a blank panel fitted to the front and the rear.

As standard frames operate with 230V 50Hz. (Other voltages available to special order.)

Features

- Compact, rugged & dependable frames.
- Up to 9 modules & associated rear connectors in the 5AV2645 2U rack-mounting frame, 4 in the 5AV2641 frame and 2 in the portable case.
- 5AV2642X portable case with integral XLRs also available.
- All 2600 modules are independently mains powered maximising reliability & isolation between modules

2600 range frames



Specification	<i>5AV2645 2U frame</i>	<i>5AV2641 1U frame</i>	<i>5AV2642 portable case</i>
Maximum number of modules	9	4	2
Height	2U (88mm)	1U (44mm)	60mm
Width	19" (478mm)	19" (478mm)	180mm
Depth	420mm	420mm	410mm
Weight	4.4Kg	5.5Kg	2.3Kg
Connector	IEC	IEC	IEC
Maximum current	1A	500mA	250mA
Power requirement		230V 50Hz standard	

Ordering information	
5AV2645	2U 19" rack mounting frame for up to 9 modules
5AV2641	1U 19" rack mounting frame for up to 4 modules
5AV2642	Portable case for up to 2 modules
5AV2642X	Portable case with XLRs for up to 2 modules
9MW264540	Blank panel (front or rear)

We reserve the right to change technical specifications without prior notice. E&OE.

LOCAL
DISTRIBUTOR

DTL Broadcast Ltd
Johnson's Estate, Silverdale Road,
Hayes, Middx, UB3 3BA, UK.
Phone: +44 (0) 20 8813 5200 Fax: +44 (0) 20 8813 5022
Internet: www.dtl-broadcast.com Email: info@dtl-broadcast.com