



Description

Frame for mounting up to 14 *MiniBlox* units in a 19" rack within 2RU of rack space.

MiniBlox units slide into guides & mate with power connectors that are bussed to the central power supply.

The frame requires one or two 4021 central power supplies which are fitted from the rear of the frame.

LEDs on front panel show power supply status.

Power supplies accept 100-240VAC at 47-63Hz and have IEC320 C14 mains inlets for worldwide operation. They comply with all major international standards including CE and UL.

www.miniblox.com

Specifications

Frame

Number of MiniBlox units 14 maximum
Number of power supplies required 1 or 2

Power supply

Input connectors IEC320 C14
Input voltage 100-240VAC
Input frequency 47-63Hz
Input current 1.9A
Standards All major international standards including CE and UL
Temperature range 0°C to 40°C at maximum load

Other

Dimensions 88mm (2U) x 478mm (19") x 430mm
Weight Frame 1Kg – power supply 750g

Ordering information

4020 2U rack mounting frame for up to 14 units with single or dual power supplies

4021 Central power supply for 4020 2U rack mounting frame

We reserve the right to change technical specifications without prior notice. E&OE.

DTL Broadcast Ltd, Johnson's Estate, Silverdale Road, Hayes, Middlesex, UB3 3BA, UK.

Phone: +44 (0) 20 8813 5200 Fax: +44 (0) 20 8813 5022 Internet: www.dtl-broadcast.com Email: sales@dtl-broadcast.com