

DTL MiniBloxTM

4600B Balanced AES-EBU audio DA



Features

- Balanced AES3 110Ω input
- Four balanced AES3 110Ω outputs
- One unbalanced AES3-id 75Ω output
- Automatically equalises over 250m of audio cable
- Supports data rates from 32 to 192kHz
- Transformer coupling on input and outputs for good common mode and isolation performance
- Compact and rugged design
- Locking connector for PSU

Description

The 4600B Balanced AES-EBU audio DA accepts and automatically equalises one balanced input and provides four balanced outputs and one unbalanced output.

It is housed in an extremely compact and rugged aluminium case ideally suited to both studio and portable applications.

www.miniblox.com

Specifications

Input

Type	Transformer coupled
Standard	110Ω AES3-2003
Connector	9 way D type socket
Return loss	>40dB (0.1 to 6MHz)
Signal level	2-7V p-p
Max cable length	>250m
Sample Rate	32 – 192 kHz

Balanced outputs

Number	Four transformer coupled
Standard	110Ω AES3-2003
Connector	9 way D type socket
Return loss	>32dB (0.1 to 6MHz)
Signal level	2-7V p-p

Unbalanced output

Number	One
Standard	75Ω AES3-id (SMPTE 276M)
Connector	BNC
Return loss	>32dB (0.1 to 6MHz)
Level	1V p-p ±10%
Power	
Voltage	6-12V DC
Current	150mA at 6V
Power Connector	Locking 2.5mm jack connector (centre +ve)
Other	
LED	Green for AES lock, red AES out-of lock
Temperature range	0°C to 40°C
Dimensions	63.5mm x 84mm x 30mm (excluding connectors)
Weight	150g

Ordering information

4600B	Balanced AES-EBU audio DA	4006	Desktop power supply with IEC320 C14 inlet
4010	1U rack mounting frame for up to 5 units including PSU		

We reserve the right to change technical specifications without prior notice. E&OE.

DTL Broadcast Ltd, Johnson's Estate, Silverdale Road, Hayes, Middlesex, UB3 3BA, UK.

Phone: +44 (0) 20 8813 5200 Fax: +44 (0) 20 8813 5022 Internet: www.dtl-broadcast.com Email: sales@dtl-broadcast.com